

 $Drg\ No.\ TS-5500$  < use this ref for downloading from our website

Title: Traditional Aluminium Glazing Bar system
Verge detail lead flashing to brickwork

Scale: 1:2

download from www.patent-glazing.com/pdf/traditional --- for .pdf format download from www.patent-glazing.com/cad/traditional --- for .dwg format

## Key:-

- 1. TC extruded aluminium Traditional Glazing Bar with fin gasket ~ by SPG Co Ltd
- 2. CT extruded aluminium Traditional Pressure Cap with fin gasket fixed to glazing bar with No 10 self tappers at 300mm centres with optional extruded aluminium CT0 type Cover Cap ~ by SPG Co Ltd
- 3. 6mm to 10mm thick infill ~ by SPG Co Ltd
- 4. Styrofoam lead support between glazing bar and wall ~ by SPG Co Ltd
- 5. Code 4 lead flashing chasing out to brickwork and pointing  $\sim \frac{\text{NOT}}{\text{NOT}}$  by SPG Co Ltd. Dressing of lead flashing over aluminium flashing  $\sim$  by SPG Co Ltd
- 6. 1.5mm thick aluminium packing piece ~ by SPG Co Ltd
- 7. Internal wall finishings NOT by SPG co Ltd.

