

 $Drg\ No.\ TS-5540$ < use this ref for downloading from our website

Title: Traditional Aluminium Glazing Bar System
Verge detail above slate line with lead flashing

Scale: 1:2

download from www.patent-glazing.com/pdf/traditional --- for .pdf format download from www.patent-glazing.com/cad/traditional --- for .dwg format

Key:-

- 1. TC Extruded aluminium Traditional Glazing Bar with Fin gasket~ by SPG Co Ltd
- 2. CT Extruded aluminium Traditional Tressure Cap with fin gasket assembled to glazing bars with No. 10 self tappers at 300mm centres with optional extruded aluminium Cover Cap ~ by SPG Co Ltd
- 3. 6mm to 10mm thick infill ~ by SPG Co Ltd
- 4. 1.5mm aluminium packing piece ~ by SPG Co Ltd
- 5. Styrofoam support for lead flashing between glazing system and wall ~ by SPG Co Ltd
- 6. Timber support for lead flashings. ~ NOT by SPG Co Ltd
- 7. Code 4 lead flashings dressed over timber support $\sim \frac{\text{NOT}}{\text{NOT}}$ by SPG Co Ltd. Dressing of lead flashing over aluminium flashing \sim by SPG Co Ltd
- 8. Internal wall finishing ~ NOT by SPG Co Ltd.
- 9. Timber roof supports ~ NOT by SPG Co Ltd
- 10. Tiled / slated roof ~ NOT by SPG Co Ltd

